

# Highline 1100 på WT - Vævet tekstil

## Produktbeskrivelse



**ege**

THE URGE TO EXPLORE SPACE

| Produktbeskrivelse  | Metoder          | Produktdata                    |
|---------------------|------------------|--------------------------------|
| <b>Konstruktion</b> |                  |                                |
| Struktur            | ISO 2424         | Tuftet cut pile                |
| Gauge               | ISO 2424         | 1/8                            |
| Luvmateriale        | DIR 96/73, 96/74 | 100% regenerated Econyl<br>PA6 |
| Farvemethode        | -                | Millitron farvet               |
| Bagside             | eTL              | WT - Vævet tekstil             |
| Dimensioner         | ISO 3018         | Approx. 400 cm                 |
| Totalhøjde          | ISO 1765         | Ca. 8,0 mm.                    |
|                     | .                | 0.32"                          |
| Slidlag             | ISO 1766         | Ca. 5,5 mm.                    |
| Noppeantal          | ISO 1763         | Ca. 197.100 pr.m2              |
| Totalvægt           | ISO 8543         | Ca. 2.550 g/m2                 |
|                     | .                | 75.2 oz./yd2                   |
| Luvindsatsvægt      | eTL              | 1.100 g/m2                     |
|                     | .                | 32.45 oz./yd2                  |
| Luvdensitet         | ISO 8543.        | Ca. 0,155 g/cm3                |

### Egnethedsprøvnings

|                                |                                    |                             |
|--------------------------------|------------------------------------|-----------------------------|
| Brugsområder                   | EN 1307                            | 33 - Erhverv - Kraftig brug |
| Garanti                        | eTL                                | Contract certifikat         |
| Brugsområder                   | Gulvbranchen                       | Klasse 33                   |
| Rullehjulsegnet                | EN 985                             | Ja, konstant brug           |
| Trappeegnet                    | EN 1963                            | Ja                          |
| Antistatiske egenskaber        | eTL                                | Permanent antistatisk       |
| Personopladning                | EN 1815                            | Antistatisk                 |
| Trinlydsdæmpning               | ISO 717-2                          | 27 dB                       |
| Akustisk absorption            | ISO 354                            | 0,20 aW                     |
| Gulvarmeegnet                  | eTL                                | Ca. 0,14 m2K/W              |
| Lysrefleksion                  | eTL                                | Testrapport                 |
| Lysægthed                      | ISO 105-B02                        | >5                          |
|                                | AATCC 16                           | 5.0                         |
| Gnideægthed våd                | ISO 105-X12                        | >3                          |
|                                | AATCC 165                          | 5.0                         |
| Gnideægthed tør                | ISO 105-X12                        | >3-4                        |
|                                | AATCC 165                          | 5.0                         |
| Vandægthed mønstrede/melerede  | ISO 105-E01                        | >4                          |
| Cleaning                       | AATCC 138                          | 5.0                         |
| Colour fast.Oxides of nitrogen | AATCC 164                          | 5.0                         |
| Øvrige brugstests              | Golf Spike Resistance Test         | 3,2                         |
|                                | ASTM D5252 Hexapod                 | 4.0/ 4.0                    |
|                                | -                                  | Commercial - Heavy          |
|                                | AATCC 134 Electrostatic propensity | 3.1 kV                      |

### Sikkerhed & Miljø

|                     |                      |          |
|---------------------|----------------------|----------|
| Brandklassifikation | VKF/AEAI             | Godkendt |
|                     | BS 6853, NF X 70-100 | Godkendt |

**ege**

THE URGE TO EXPLORE SPACE

| Produktbeskrivelse        | Metoder                        | Produktdata                 |
|---------------------------|--------------------------------|-----------------------------|
| CE Mærkning               | ASTM E-648                     | Class 1                     |
|                           | ASTM E662 Smoke Density        | <450                        |
|                           | ASTM D2859 Surface Flamm.      | Pass                        |
|                           | CAN,ULC-S102.2                 | FSC1 66                     |
|                           | Polen std.                     | OK                          |
|                           | EN 13501-1 Euroclass           | Cfl-s1                      |
|                           | HU,MSZ 14800-9:1985            | Godkendt                    |
|                           | Kina                           | Cfl-s1,t0                   |
|                           | EN 14041                       | Certificeret                |
|                           | CPR                            | 1021-CPR-006-2/16           |
|                           | Ydeevnedeklaration             | DOP 1C-PA-WT                |
|                           | Notified body no.              | 1021                        |
|                           | Ce Year                        | 07                          |
|                           | Content of PCP EN 12673        | DL                          |
| Indeklima                 | Formaldehyde emission          | NA                          |
|                           | Skridsikkerhed EN 13893        | Class DS                    |
|                           | M1                             | Med WTA bagside             |
|                           | INSTA 800                      | Støvniveau 5                |
|                           | BASTA                          | Registreret                 |
|                           | Green Label Plus               | Godkendt                    |
|                           | Green Label Singapore          | Godkendt                    |
|                           | Emissions dans l'air intérieur | A+/A+                       |
|                           | Indoor Air Comfort Gold        | Group 3                     |
|                           | ABG                            | ABG-28-01-03-01-2018        |
| Miljø                     | BRE                            | ENP 434                     |
|                           | Byggvarudeklaration            | eBVD                        |
|                           | Environmental Product Decl.    | EPD-EGE-2013103-CBC1-EN     |
|                           | Cradle To Cradle Certified     | Bronze certified            |
|                           | Recycled Content, ISO 14021    | Ca. 42,0 %                  |
|                           | Recycled Content for LEED      | Ca. 32,0 %                  |
|                           | LEED                           | Qualified                   |
|                           |                                |                             |
| <b>Vejledninger</b>       |                                |                             |
| Montering, inkl. limguide | DK                             | Dansk                       |
|                           | N                              | Norsk                       |
|                           | S                              | Svensk                      |
|                           | GB                             | English                     |
|                           | D                              | Deutsch                     |
|                           | F                              | Français                    |
| Rengøring, pletfjerning   | DK                             | Dansk                       |
|                           | N                              | Norsk                       |
|                           | S                              | Svensk                      |
|                           | GB                             | English                     |
|                           | D                              | Deutsch                     |
|                           | F                              | Français                    |
| <b>Producent</b>          |                                |                             |
| Fabriks certificering     | ISO 9001                       | Audited and verified by BVC |

| <b>Produktbeskrivelse</b> | <b>Metoder</b> | <b>Produktdata</b>            |
|---------------------------|----------------|-------------------------------|
|                           | ISO 14001      | Audited and verified by BVC   |
|                           | EMAS           | Audited and verified by BVC   |
|                           | DS/OHSAS       | Audited and verified by BVC   |
|                           | DS 49001       | Audited and verified by BVC   |
|                           | CRuk           | Member of Carpet Recycling UK |

**ege**

THE URGE TO EXPLORE SPACE