

# Highline 1100 på WT - Vævet tekstil

## Produktbeskrivelse



**ege**

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
<b>Konstruktion</b>		
Struktur	ISO 2424	Tuftet cut pile
Gauge	ISO 2424	1/8
Luvmateriale	DIR 96/73, 96/74	100% regenerated Econyl PA6
Farvemethode	-	Millitron farvet
Bagside	eTL	WT - Vævet tekstil
Dimensioner	ISO 3018	Approx. 400 cm
Totalhøjde	ISO 1765	Ca. 8,0 mm.
	.	0.32"
Slidlag	ISO 1766	Ca. 5,5 mm.
Noppeantal	ISO 1763	Ca. 197.100 pr.m2
Totalvægt	ISO 8543	Ca. 2.550 g/m2
	.	75.2 oz./yd2
Luvindsatsvægt	eTL	1.100 g/m2
	.	32.45 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,155 g/cm3

### Egnethedsprøvnings

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
Garanti	eTL	Contract certifikat
Brugsområder	Gulvbranchen	Klasse 33
Rullehjulsegnet	EN 985	Ja, konstant brug
Trappeegnet	EN 1963	Ja
Antistatiske egenskaber	eTL	Permanent antistatisk
Personopladning	EN 1815	Antistatisk
Trinlydsdæmpning	ISO 717-2	27 dB
Akustisk absorption	ISO 354	0,20 aW
Gulvarmeegnet	eTL	Ca. 0,14 m2K/W
Lysrefleksion	eTL	Testrapport
Lysægthed	ISO 105-B02	>5
	AATCC 16	5.0
Gnideægthed våd	ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed mønstrede/melerede	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Øvrige brugstests	Golf Spike Resistance Test	3,2
	ASTM D5252 Hexapod	4.0/ 4.0
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	3.1 kV

### Sikkerhed & Miljø

Brandklassifikation	VKF/AEAI	Godkendt
	BS 6853, NF X 70-100	Godkendt

**ege**

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata	
CE Mærkning	ASTM E-648	Class 1	
	ASTM E662 Smoke Density	<450	
	ASTM D2859 Surface Flamm.	Pass	
	CAN,ULC-S102.2	FSC1 66	
	Polen std.	OK	
	EN 13501-1 Euroclass	Cfl-s1	
	HU,MSZ 14800-9:1985	Godkendt	
	Kina	Cfl-s1,t0	
	EN 14041	Certificeret	
	CPR	1021-CPR-006-2/16	
	Ydeevnedeklaration	DOP 1C-PA-WT	
	Notified body no.	1021	
	Ce Year	07	
	Content of PCP EN 12673	DL	
	Formaldehyde emission	NA	
Indeklima	Skridsikkerhed EN 13893	Class DS	
	M1	Med WTA bagside	
	INSTA 800	Støvniveau 5	
	BASTA	Registreret	
	Green Label Plus	Godkendt	
	Green Label Singapore	Godkendt	
	Emissions dans l'air intérieur	A+/A+	
	Indoor Air Comfort Gold	Group 3	
	ABG	ABG-28-01-03-01-2018	
	BRE	ENP 434	
Miljø	Byggvarudeklaration	eBVD	
	Environmental Product Decl.	EPD-EGE-2013103-CBC1-EN	
	Cradle To Cradle Certified	Bronze certified	
	Recycled Content, ISO 14021	Ca. 42,0 %	
	Recycled Content for LEED	Ca. 32,0 %	
	LEED	Qualified	
	<b>Vejledninger</b>		
	Montering, inkl. limguide	DK	Dansk
N		Norsk	
S		Svensk	
GB		English	
D		Deutsch	
F		Français	
Rengøring, pletfjerning	DK	Dansk	
	N	Norsk	
	S	Svensk	
	GB	English	
	D	Deutsch	
	F	Français	
<b>Producent</b>			
Fabriks certificering	ISO 9001	Audited and verified by BVC	

<b>Produktbeskrivelse</b>	<b>Metoder</b>	<b>Produktdata</b>
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

**ege**

THE URGE TO EXPLORE SPACE