


# ReForm Foss Broadloom

## Produktbeskrivelse



**ege**

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
<b>Konstruktion</b>		
Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	1/10
Luvmateriale	DIR 96/73, 96/74	100% regenerated Econyl PA6
Farvemethode	-	Millitron farvet
Bagside	eTL	WT - Vævet tekstil
Dimensioner	ISO 3018	Approx. 400 cm
Totalhøjde	ISO 1765	Ca. 5,5 mm.
	.	0.22"
Slidlag	ISO 1766	Ca. 3,0 mm.
Noppeantal	ISO 1763	Ca. 173.000 pr.m2
Totalvægt	ISO 8543	Ca. 2.050 g/m2
	.	60.5 oz./yd2
Luvindsatsvægt	eTL	440 g/m2
Luvdensitet	ISO 8543.	Ca. 0,100 g/cm3

### Egnethedsprøvnings

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
Garanti	eTL	Contract certifikat
Brugsområder	Gulvbranchen	Klasse 33
Rullehjulseget	EN 985	Ja, konstant brug
Trappeget	eTL	Ja
Antistatiske egenskaber	eTL	Permanent antistatisk
Personopladning	EN 1815	Antistatisk
Trinlydsdæmpning	ISO 717-2	21 dB
Akustisk absorption	eTL	0,20 aW
Gulvarmeegnet	eTL	Ca. 0,09 m2K/W
Lysrefleksion	eTL	Testrapport
Lysægthed	ISO 105-B02	5
	AATCC 16	4.5
Gnideægthed våd	ISO 105-X12	4-5
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	5
	AATCC 165	5.0
Vandægthed mønstrede/melerede	ISO 105-E01	4
Cleaning	AATCC 138	4.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Øvrige brugstests	ASTM D5252 Hexapod	3.0/2.5
	-	Commercial - Heavy

### Sikkerhed & Miljø

Brandklassifikation	VKF/AEAI	Godkendt
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1

Produktbeskrivelse	Metoder	Produktdata
CE Mærkning	EN 14041	Certificeret
	CPR	1021-CPR-006-2/16
	Ydeevnedeklaration	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	07
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Skridsikkerhed EN 13893	Class DS
Indeklima	M1	Med WTA bagside
	BASTA	Registreret
	Green Label Plus	Godkendt
	Emissions dans l'air intérieur	A+/A+
	ABG	ABG-28-01-03-01-2018
Miljø	Byggvarudeklaration	eBVD
	Environmental Product Decl.	EPD-EGE-20160001-CCA1-EN
	Cradle To Cradle Certified	Bronze certified
	Recycled Content, ISO 14021	Ca. 26,0 %
	Recycled Content for LEED	Ca. 21,0 %
	LEED	Qualified

### Vejledninger

Montering, inkl. limguide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Producent

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE