

ReForm Foss Broadloom

Produktbeskrivelse



| Produktbeskrivelse | Metoder | Produktdata |
|---------------------|------------------|--------------------------------|
| Konstruktion | | |
| Struktur | ISO 2424 | Tuftet loop pile |
| Gauge | ISO 2424 | 1/10 |
| Luvmateriale | DIR 96/73, 96/74 | 100% regenerated Econyl PA6 |
| Farvemethode | - | Millitron farvet |
| Bagside | eTL | WT - Vævet tekstil |
| Dimensioner | ISO 3018 | Approx. 400 cm |
| Totalhøjde | ISO 1765 | Ca. 5,5 mm. |
| | . | 0.22" |
| Slidlag | ISO 1766 | Ca. 3,0 mm. |
| Noppeantal | ISO 1763 | Ca. 173.000 pr.m2 |
| Totalvægt | ISO 8543 | Ca. 2.050 g/m2 |
| | . | 60.5 oz./yd2 |
| Luvindsatsvægt | eTL | 440 g/m2 |
| Luvdensitet | ISO 8543. | Ca. 0,100 g/cm3 |

Egnethedsprøvnings

| | | |
|--------------------------------|------------------------------------|-----------------------------|
| Brugsområder | EN 1307 | 33 - Erhverv - Kraftig brug |
| Garanti | eTL | Contract certifikat |
| Brugsområder | Gulvbranchen | Klasse 33 |
| Rullehjulseget | EN 985 | Ja, konstant brug |
| Trappeget | eTL | Ja |
| Antistatiske egenskaber | eTL | Permanent antistatisk |
| Personopladning | EN 1815 | Antistatisk |
| Trinlydsdæmpning | ISO 717-2 | 21 dB |
| Akustisk absorption | eTL | 0,20 aW |
| Gulvarmeegnet | eTL | Ca. 0,09 m2K/W |
| Lysægthed | ISO 105-B02 | 5 |
| | AATCC 16 | 4.5 |
| Gnideægthed våd | ISO 105-X12 | 4-5 |
| | AATCC 165 | 5.0 |
| Gnideægthed tør | ISO 105-X12 | 5 |
| | AATCC 165 | 5.0 |
| Vandægthed mønstrede/melerede | ISO 105-E01 | 4 |
| Cleaning | AATCC 138 | 4.0 |
| Colour fast.Oxides of nitrogen | AATCC 164 | 5.0 |
| Øvrige brugstests | ASTM D5252 Hexapod | 3.0/2.5 |
| | - | Commercial - Heavy |
| | AATCC 134 Electrostatic propensity | 1.1 kV |

Sikkerhed & Miljø

| | | |
|---------------------|---------------------------|----------|
| Brandklassifikation | VKF/AEAI | Godkendt |
| | ASTM E-648 | Class 1 |
| | ASTM E662 Smoke Density | <450 |
| | ASTM D2859 Surface Flamm. | Pass |
| | EN 13501-1 Euroclass | Cfl-s1 |

| Produktbeskrivelse | Metoder | Produktdata |
|--------------------|--------------------------------|--------------------------|
| CE Mærkning | EN 14041 | Certificeret |
| | CPR | 1021-CPR-006-2/16 |
| | Ydeevnedeklaration | DOP 1C-PA-WT |
| | Notified body no. | 1021 |
| | Ce Year | 07 |
| | Content of PCP EN 12673 | DL |
| | Formaldehyde emission | NA |
| | Skridsikkerhed EN 13893 | Class DS |
| Indeklima | M1 | Med WTA bagside |
| | BASTA | Registreret |
| | Green Label Plus | Godkendt |
| | Emissions dans l'air intérieur | A+/A+ |
| | Indoor Air Comfort Gold | Group 3 |
| | ABG | ABG-28-01-03-01-2018 |
| | BRE | ENP 434 |
| Miljø | Environmental Product Decl. | EPD-EGE-20160001-CCA1-EN |
| | Recycled Content, ISO 14021 | Ca. 26,0 % |
| | Recycled Content for LEED | Ca. 21,0 % |

Vejledninger

| | | |
|---------------------------|----|----------|
| Montering, inkl. limguide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Français |
| Rengøring, pletfjerning | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Français |

Producent

| | | |
|----------------------|-----------|-------------------------------|
| Fabrikscertificering | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | DS/OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |



THE URGE TO EXPLORE SPACE