


ReForm Legend Ecotrust

Produktbeskrivelse



ege

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
Konstruktion		
Struktur	ISO 2424	Tuftet loop pile strukturvævet
Gauge	ISO 2424	1/12
Luvmateriale	DIR 96/73, 96/74	100% regenerated Econyl PA6
Farvemethode	-	Millitron farvet
Bagside	eTL	Ecotrust 350, 100% recycled
Dimensioner	ISO 3018	48x48/96x96/24x96cm/Figura
Dimensionstabilitet fliser	EN 986	<0,2%
Totalhøjde	ISO 1765	Ca. 8,5 mm.
	.	0.34"
Slidlag	ISO 1766	Ca. 4,0 mm.
Noppeantal	ISO 1763	Ca. 213.000 pr.m2
Totalvægt	ISO 8543	Ca. 3.050 g/m2
	.	89.9 oz./yd2
Luvindsatsvægt	eTL	950 g/m2
	.	28.03 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,175 g/cm3
Biocidal treatment	Biocidal Product Regulation	Contains preser.to antagonize

Egnethedsprøvnninger

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
Garanti	eTL	Contract certifikat
Brugsområder	Gulvbranchen	Klasse 33
Rullehjulsegnet	EN 985	Ja, konstant brug
Trappeegnet	EN 1963	Ja
Antistatiske egenskaber	eTL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	ISO 717-2	27 dB
Akustisk absorption	ISO 354	0,30 aW
Gulvarmeegnet	eTL	Ca. 0,15 m2K/W
Lysrefleksion	eTL	Testrapport
Lysægthed	ISO 105-B02	>5
	AATCC 16	5.0
Gnideægthed våd	ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed mønstrede/melerede	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	4.0
Øvrige brugstests	ASTM D5252 Hexapod	4.0/ 4.5
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	3.5 kV

Sikkerhed & Miljø

Brandklassifikation	VKF/AEAI	Godkendt
---------------------	----------	----------

ege

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
CE Mærkning	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	EN 14041	Certificeret
	CPR	1021-CPR-010-1/16
	Ydeevnedeklaration	DOP 5B-PA-ECT350
	Notified body no.	1021
	Ce Year	14
	Content of PCP EN 12673	DL
Indeklima	Formaldehyde emission	NA
	Skridsikkerhed EN 13893	Class DS
	M1	Med ECTA bagside
	RUSLAND	Godkendt
	BASTA	Registreret
	Green Label Plus	Godkendt
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 3
	ABG	ABG-28-01-03-03-2018
	Miljø	BRE
BREEAM-NOR		Med ECTA bagside
Environmental Product Decl.		20150334-CCA1-EN
Cradle To Cradle Certified		Bronze certified
Recycled Content, ISO 14021		Ca. 47,0 %
Recycled Content for LEED		Ca. 39,0 %
LEED		Qualified

Vejledninger

Montering, inkl. limguide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Montering fliser	Lægningsretning	Quarter turn/ monolithic
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Producent

Fabriks certificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC



THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
	CRuk	Member of Carpet Recycling UK

ege

THE URGE TO EXPLORE SPACE