

Texture Care

Produktbeskrivelse



ege

THE URGE TO EXPLORE SPACE

Produktbeskrivelse	Metoder	Produktdata
Konstruktion		
Struktur	ISO 2424	Tuftet cut pile
Gauge	ISO 2424	1/8
Luvmateriale	DIR 96/73, 96/74	100% polypropylene
Farvemethode	-	Forfarvet garn
Bagside	eTL	IP - Vandfast
Dimensioner	CEN/TS 14159	Approx. 400 cm
Totalhøjde	ISO 1765	Ca. 8,0 mm.
Slidlag	ISO 1766	Ca. 5,5 mm.
Noppeantal	ISO 1763	Ca. 153.000 pr.m2
Totalvægt	ISO 8543.	Ca. 3.000 g/m2
Luvindsatsvægt	eTL	1.050 g/m2
Luvdensitet	ISO 8543.	Ca. 0,135 g/cm3
Soil protection	eTL	Nej
MRSA protection	eTL	Ja
Biocidal treatment	Biocidal Product Regulation	Contains preser.to antagonize settlement of microorganisms on the surface
Egnethedsprøvnings		
Brugsområder	EN 1307	22 - Bolig - Moderat brug
Garanti	eTL	Garanti mod gennemslid 10 år
Antistatiske egenskaber	eTL	Permanent antistatisk
Personopladning	EN 1815	Antistatisk
Trinlydsdæmpning	ISO 717-2	27 dB
Akustisk absorption	ISO 354	0,20 aW
Gulvarmeegnet	eTL	Ca. 0,14 m2K/W
Lysrefleksion	eTL	Testrapport
Lysægthed	ISO 105-B02	>5
Gnideægthed våd	ISO 105-X12	>3
Gnideægthed tør	ISO 105-X12	>3-4
Vandægthed mønstrede/melerede	ISO 105-E01	>4
Sikkerhed & Miljø		
Brandklassifikation	Japan	Godkendt
	EN 14041	Efl
CE Mærkning	EN 14041	Certificeret
	Ydeevnedeklaration	DOP E
	Notified body no.	NA
	Ce Year	14
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Skridsikkerhed EN 13893	Class DS
Indeklima	NHS patient area tests	Godkendt
Miljø	BRE	ENP 434
Vejledninger		
Montering, inkl. limguide	DK	Dansk

Produktbeskrivelse	Metoder	Produktdata
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Rengøring, pletfjerning	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Producent

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

ege

THE URGE TO EXPLORE SPACE